

PICKERING XSV 3000
CARTRIDGE REPAIR TEST REPORT

MM!

REWIND COILS

MATERIAL:

- OFC COPPER WIRE – SILVER WIRE
- REPLACE RUBBER DAMPER YES NO

RETIP SERVICE

STYLUS TYPE :

- CONICAL 15um-18um
- ELLIPTICAL 5/18 um 8/18 um
- BIRADIAL ELLIPTICAL
- FRITZ GYGER II
- FRITZ GYGER S
- MICRORIDGE
- FINELINE, MICROLINE
- BONDED---JOINTED---NUDE---

CANTILEVER TYPE:

- ALUMINIUM BORON RUBY TAMPED

MEASURING RESULT:

- TRACKING ABILITY HORIZONTAL : 80um 12gr
- TRACKING ABILITY VERTICAL : 50um 12gr
- FREQUENCY RESPONSE : 20-18000Hz $\pm 3dB$
- INTERNAL COIL RESISTANCE : —
- OUTPUT VOLTAGE AT 1000 Hz, 8 cm/sec : —
- CHANNEL BALANCE : 2.5dB
- NOTE: MM MOVING MAGNET

MEASURING UNITS:

- TONEARM: SME III, TECHNICS SL1210, ORTOFON SK212, EMT 929 (Only EMT cart.)
- TURNTABLE: THORENS TD145, EMT 930 (only EMT cart.)
- TEST RECORDS: DHFI, CLEARAUDIO

DATE:

2015.02.14. 